

FEATURES

- > Oil-less
- > Long life
- > Low power consumption
- > Worldwide service network
- > Low sound level/vibration
- > Protection class IP54 (AP/LP/LW-Series)
- > CE approved (230V 50Hz models with housing and cord with plug)
- > Integrated intake filter (AP/LP/LW-Series)
- > RoHS compliant

TYPICAL APPLICATIONS

- > Sewage aeration
- > Aquarium aeration
- > Gas/particle analysis
- > Air mattress
- > Compression therapy
- > Battery aeration
- > Grey water treatment
- > Process water recycling

BASE MODEL

AP
LP
LW
YP
YP-DU



Linear

Linear Diaphragm Pumps


PRODUCT OVERVIEW

Model	Pressure	Vacuum	without housing		Flow at rated pressure										Page			
			without housing	with housing	0	50	100	150	200	250	300	400(l/min)						
 YP-15DU	•			•													15 l/min @ 100 mbar	3
 YP-50DU	•			•													50 l/min @ 120 mbar	4
 YP-40VC YP-70VC	•	•		•													43 (39) l/min @ 120 (-120) mbar 73 (64) l/min @ 120 (-180) mbar	5
 AP-40 AP-60N AP-60/80 AP-80H AP-100 AP-120	•			•													45 l/min @ 120 mbar 47 l/min @ 200 mbar 60 l/min @ 200 mbar 82 l/min @ 200 mbar 108 l/min @ 200 mbar 125 l/min @ 200 mbar	6,7
 LP-150HN LP-200HN	•			•													150 l/min @ 200 mbar 200 l/min @ 200 mbar	8
 LW-240 LW-300 LW-400	•			•													240 l/min @ 200 mbar 350 l/min @ 200 mbar 425 l/min @ 200 mbar	9

Linear Diaphragm Pumps YP-15DU

Flow at rated pressure

15 l/min at 100 mbar



PNEUMATIC DATA

Description	YP-15DU
Part number	52500016
Flow at rated pressure	15 l/min
Rated pressure	100 mbar
Operating range	20 to 200 mbar

ELECTRICAL DATA

Motor type	Linear drive
Voltage	230V 50Hz
Power consumption at rated pressure	13 W

GENERAL DATA

Ambient temperature	-10 to 40 °C
Weight	1.2 kg
Outlet diameter	2 x 8 mm
Average sound level	38 dB (A)

SERVICE PARTS


Chamber block set ¹⁾	700017
---------------------------------	--------

All listed values are measured at standard atmospheric conditions.

If 230V 60Hz is required, please consult factory.

1) Denotes that service part is only available for trained service personnel.

FLOW CURVES



SUPPLIED AS STANDARD

- 2 x Leads (30 cm) for power supply
- 1 x Lead (10 cm) for earth/ground

SERVICE PARTS

- Chamber block set¹⁾ consists of:
- 2 x Pump head with valves
 - 2 x Diaphragm assembly
 - 2 x Diaphragm nut
 - 2 x Diaphragm washer



5250... Stock programme

Note: Operation outside specified operating range is not recommended.
All listed values are measured at standard atmospheric conditions.

Linear Diaphragm Pump YP-50DU

Flow at rated pressure

50 l/min at 120 mbar



YP-30/40/50DU

PNEUMATIC DATA

Description	YP-50DU
Part number	52500052
Flow at rated pressure	50 l/min
Rated pressure	120 mbar
Operating range	50 to 200 mbar

ELECTRICAL DATA

Motor type	Linear drive
Voltage	230V 50Hz
Power consumption at rated pressure	45 W

GENERAL DATA

Ambient temperature	-10 to 40 °C
Weight	2.8 kg
Outlet diameter	2 x 10 mm
Average sound level	50 dB (A)

SERVICE PARTS


Chamber block set ¹⁾	700020
---------------------------------	---------------

All listed values are measured at standard atmospheric conditions.

If 230v 60Hz is required, please consult factory.

1) Denotes that service part is only available for trained service personnel.

FLOW CURVES



SUPPLIED AS STANDARD

- 2 x Leads (30 cm) for power supply
- 1 x Lead (10 cm) for earth/ground

SERVICE PARTS

- Chamber block set¹⁾ consists of:
- 2 x Pump head with valves
 - 2 x Diaphragm assembly
 - 2 x Diaphragm nut
 - 2 x Diaphragm washer


5250... Stock programme

Note: Operation outside specified operating range is not recommended.
All listed values are measured at standard atmospheric conditions.

Linear Diaphragm Pumps YP-40VC, YP-70VC

Flow at rated pressure

43 to 73 l/min at 120 to 200 mbar



YP-30/40/50/60/70VC

PNEUMATIC DATA

Description	YP-40VC	YP-70VC
Part number	52500402	52500073
Flow at rated pressure	43 l/min	73 l/min
Rated pressure	±120 mbar	±120 mbar
Operating range	-200 to 200 mbar	-200 to 200 mbar

ELECTRICAL DATA

Motor type	Linear drive	Linear drive
Voltage	230V 50Hz	230V 50Hz
Power consumption at rated pressure	40 W	85 W

GENERAL DATA

Ambient temperature	-10 to 40 °C	-10 to 40 °C
Weight	5.1 kg	6.2 kg
Inlet/Outlet diameter	Rc 3/8	Rc 3/8
Average sound level	39 dB (A)	48 dB (A)


SERVICE PARTS

Chamber block set ¹⁾	700020	700038
---------------------------------	---------------	---------------

All listed values are measured at standard atmospheric conditions.
If 230V 60Hz is required, please consult factory.

1) Denotes that service part is only available for trained service personnel.
Please refer to the operation manual for additional information.

FLOW CURVES



Note: Operation outside specified operating range is not recommended.
All listed values are measured at standard atmospheric conditions.

SUPPLIED AS STANDARD

Cable/Euro-plug

SERVICE PARTS

Chamber block set¹⁾ consists of:
2 x Pump head with valves
2 x Diaphragm assembly
2 x Diaphragm nut
2 x Diaphragm washer

ACCESSORIES



Tube connector I.D. 14 mm
(part number 31644)

5250... Stock programme

Linear Diaphragm Pump AP-40

Flow at rated pressure

45 l/min at 120 mbar



PNEUMATIC DATA

Description	AP-40
Part number	52500453
Flow at rated pressure	45 l/min
Rated pressure	120 mbar
Operating range	50 to 200 mbar

ELECTRICAL DATA

Motor type	Linear drive
Nominal Voltage	230V 50Hz
Consumption at rated pressure	0.34 A / 29 W
Efficiency at rated pressure	0.64 W/l

GENERAL DATA

Ambient temperature	-10 to 40 °C
Weight	4.3 kg
Outlet diameter	18 mm
Average sound level	34 dB (A)


SERVICE PARTS

Chamber block set ¹⁾	700580
Air filter and gasket kit	700582
Air filter kit	700583

All listed values are measured at standard atmospheric conditions.
If 230V 60Hz is required, please consult factory.

1) Denotes that service part is only available for trained service personnel.
Please refer to the operation manual for additional information.

FLOW CURVES



Note: Operation outside specified operating range is not recommended.
All listed values are measured at standard atmospheric conditions

SERVICE PARTS

Chamber block set¹⁾ consists of:
2 x Pump head with valves
2 x Diaphragm assembly
2 x Diaphragm gasket
2 x Nut
2 x Washer

Air filter and gasket kit consists of:
1 x Air cleaner element
1 x Air cleaner gasket
1 x Cover plate gasket
1 x Noise absorbing net
1 x Tank gasket

Air filter kit consists of:
5 x Air cleaner element
5 x Air cleaner gasket

SUPPLIED AS STANDARD



Cable/Euro-plug
Air connector consists of (part number 700073)
1 x Outlet hose, angled, 170/50 mm
2 x Hose clamp

5250... Stock programme

Linear Diaphragm Pumps AP-60N, AP-60/80, AP-80H, AP-100, AP-120

Flow at rated pressure

47 to 125 l/min at 200 mbar



AP-Series

PNEUMATIC DATA

Description	AP-60N	AP-60/80	AP-80H	AP-100	AP-120
Part number	52500478	52500485	52500480	52500472	52500473
Flow at rated pressure	47 l/min	60 l/min	82 l/min	108 l/min	125 l/min
Rated pressure	200 mbar				
Operating range	100 to 300 mbar	100 to 300 mbar	100 to 300 mbar	140 to 300 mbar	160 to 300 mbar

ELECTRICAL DATA

Motor type	Linear drive	Linear drive	Linear drive	Linear drive	Linear drive
Nominal Voltage	230V 50Hz	230V 50Hz	230V 50Hz	230V 50Hz	230V 50Hz
Consumption at rated pressure	0.26 A / 31 W	0.34 A / 41 W	0.8 A / 73 W	1.06 A / 99 W	1.45 A / 128 W
Efficiency at rated pressure	0.66 W/l	0.68 W/l	0.89 W/l	0.92 W/l	1.02 W/l

GENERAL DATA

Ambient temperature	-10 to 40 °C				
Weight	5.8 kg	5.8 kg	6.1 kg	6.1 kg	6.1 kg
Outlet diameter	18 mm				
Average sound level	34 dB (A)	34 dB (A)	35 dB (A)	37 dB (A)	38 dB (A)

SERVICE PARTS

Air filter and gasket kit	700582	700582	700582	700582	700582
Air filter kit	700583	700583	700583	700583	700583
*Chamber block set	700581	700581	700585	700585	700585
**Protective switch	700578	700578	700578	700578	700578

All listed values are measured at standard atmospheric conditions.


If 230V 60Hz is required, please consult factory

***Chamber block set** denotes part is only available for trained service personnel. Contact your local sales representative.

****Protective Switch** denotes that switch replacement can only be done at factory. Contact your local sales representative.

Please refer to the operation manual for additional information.

FLOW CURVES



Note: Operation outside specified operating range is not recommended.
All listed values are measured at standard atmospheric conditions

SERVICE PARTS

Air filter kit consists of
5 x Air cleaner element
5 x Air cleaner gasket

Air filter and gasket kit consists of
1 x Air cleaner element
1 x Air cleaner gasket
1 x Cover plate gasket
1 x Noise absorbing net
1 x Tank gasket

*Chamber block set consists of
2 x Pump head with valves
2 x Diaphragm assembly
2 x Diaphragm gasket
2 x Nut
2 x Washer

**Protective switch consists of
1 x Microswitch
2 x Nut
2 x Washer
1 x Cover plate gasket

SUPPLIED AS STANDARD



Cable/Euro-plug
Air connector consists of (part number 700073)
1 x Outlet hose, angled, 170/50 mm
2 x Hose clamp

5250... Stock programme

Linear Diaphragm Pumps LP-150HN, LP-200HN

Flow at rated pressure

150 to 200 l/min at 200 mbar



LP150/200HN

PNEUMATIC DATA

Description	LP-150HN	LP-200HN
Part number	52500151	52500202
Flow at rated pressure	150 l/min	200 l/min
Rated pressure	200 mbar	200 mbar
Operating range	100 to 300 mbar	100 to 300 mbar

ELECTRICAL DATA

Motor type	Linear drive	Linear drive
Nominal Voltage	230V 50Hz	230V 50Hz
Consumption at rated pressure	0.85 A/130 W	1.15 A/200 W

GENERAL DATA

Ambient temperature	-10 to 40 °C	-10 to 40 °C
Weight	8.6 kg	8.6 kg
Outlet diameter	18 mm	18 mm
Average sound level	43 dB (A)	44 dB (A)

SERVICE PARTS

Chamber block set ¹⁾	700533	700533
Air filter and gasket kit	700550	700550
Air filter kit	700551	700551
Protective switch ¹⁾	700552	700552


All listed values are measured at standard atmospheric conditions.

If 230v 60Hz is required, consult factory

1) Denotes that service part is only available for trained service personnel.

Please refer to the operation manual for additional information.

FLOW CURVES



Note: Operation outside specified operating range is not recommended.
All listed values are measured at standard atmospheric conditions

SERVICE PARTS

Chamber block set¹⁾ consists of:
 2 x Pump head with valves
 2 x Diaphragm assembly
 2 x Diaphragm nut
 2 x Diaphragm washer

Air filter and gasket kit consists of:
 1 x Air cleaner element
 1 x Air cleaner gasket
 1 x Cover plate gasket
 1 x Noise absorbing net
 1 x Tank gasket
 2 x L-Hose
 2 x L-Clamp

Air filter kit consists of:
 5 x Air cleaner element
 5 x Air cleaner gasket

Protective switch¹⁾ consists of:
 1 x Microswitch complete with cover plate
 1 x Cover plate gasket

SUPPLIED AS STANDARD

Cable/Euro-plug
 Air connector (part number 700073) consists of:
 1 x Outlet hose, angled, 170/50 mm
 2 x Hose clamp


5250... Stock programme



Linear Diaphragm Pumps LW-240, LW-300, LW-400

Flow at rated pressure

425 l/min at 200 mbar



PNEUMATIC DATA

Description	LW-240	LW-300	LW-400
Part number	52500410	52500411	52500414
Flow at rated pressure	240 l/min	350 l/min	425 l/min
Rated pressure	200 mbar	200 mbar	200 mbar
Operating range	100 to 250 mbar	100 to 250 mbar	100 to 250 mbar

ELECTRICAL DATA

Motor type	Linear drive	Linear drive	Linear drive
Nominal Voltage	230V 50Hz	230V 50Hz	230V 50Hz
Consumption at rated pressure	1.8 A/250 W	1.6 A/280 W	2.4 A/400 W

GENERAL DATA


Ambient temperature	-10 to 40 °C	-10 to 40 °C	-10 to 40 °C
Weight	14.4 kg	16.0 kg	16.0 kg
Outlet diameter	26 mm	26 mm	26 mm
Average sound level	49 db (A)	50 db (A)	51 dB (A)

SERVICE PARTS

Chamber block set ¹⁾	700500	700597	700597
Air filter and gasket kit	700502	700598	700598
Air filter kit	700510	700510	700510
Protective switch ¹⁾	700512	700599	700599

All listed values are measured at standard atmospheric conditions. Please consult factory if 230V 60Hz is needed. Please refer to the operation manual for additional information. 1) Denotes that part is only available for trained service personnel.

FLOW CURVES



Note: Operation outside specified operating range is not recommended. All listed values are measured at standard atmospheric conditions

SERVICE PARTS

Chamber block set¹⁾ consists of:
 4 x Pump head with valves
 4 x Diaphragm assembly
 4 x Diaphragm nut
 4 x Diaphragm washer

Air filter and gasket kit consists of:
 1 x Air cleaner element
 1 x Air cleaner gasket
 1 x Noise absorbing net
 1 x Tank gasket
 1 x Cover gasket
 4 x L-Hose

Air filter kit consists of:
 5 x Air cleaner element
 5 x Air cleaner gasket

Protective switch¹⁾ consists of:
 1 x Microswitch w/cover plate
 Please note: One unit is equipped with two protective switches

SUPPLIED AS STANDARD

Cable/Euro with plug
 Air connector consisting of LW-240 (700513)
 1 x Outlet hose, angled, 170/50 mm
 2 x Hose clamp
 LW-300 & LW-400 (P/N 700600)
 1 x Outlet hose, angled, 170/50 mm
 4 x Hose clamp
 1 x Relief valve assembly
 1 x Hose connector

Accessory Available:
 Air connector, straight type (P/N 700514) consists of
 1 x Outlet hose, straight, 150 mm
 2 x Hose clamp

5250... Stock programme

PUMP AND COMPRESSOR SOLUTIONS FOR OEMS WORLDWIDE

gd-thomas.com



Gardner Denver Thomas GmbH

Livry-Gargan-Str. 10
82256 Fürstenfeldbruck
Germany

T +49 8141 2280 0

F +49 8141 8892136

thomas.de@gardnerdenver.com

Gardner Denver Thomas Pneumatic Systems (Wuxi) Co. Ltd.

1 New Dong'an Road, Shuofang Town
Xinwu District, Wuxi
Jiangsu, 214142 China

T +86 510 6878 2258

F +86 510 6878 2200

thomas.cn@gardnerdenver.com

THOMAS

by Gardner Denver

Gardner Denver Thomas, Inc.

1419 Illinois Avenue
Sheboygan, WI 53081
USA

T +1 920 4574891

F +1 920 4514276

td.usa@gardnerdenver.com

The information presented in this material is based on technical data and test results of nominal units. It is believed to be accurate and reliable and is offered as an aid to help in the selection of Thomas products. It is the responsibility of the user to determine the suitability of the product for the intended use and the user assumes all risk and liability in connection therewith. Thomas does not warrant, guarantee or assume any obligation or liability in connection with this information.

Models presented in this catalog are representative of the product family. Photos of products pictured in this catalog do not necessarily represent a specific model number. To obtain further information for custom options, contact your local Thomas office.

Printed in Germany Form No. 17000162 07/2021 © Gardner Denver Thomas GmbH. All rights reserved.